HOMECRAFT SAUNAS

Sauna Heater & Spec Guide

HEATER MODEL OR KW	240V HEATERS	RECOMMENDED ROOM SIZES CUBIC FEET	CONTROL (SPECIFY INDOOR OR OUTDOOR CONTACTOR)	CIRCUIT BREAKER	ACTUAL AMPS DRAWN	WIRE SIZE 90C COPPER WIRE
4kw	Revive Slim	100-150	Tke 2-2	30	16.7	10
5kw	Revive Slim	100-250	Tke 2-2	30	20.8	10
6kw	Revive / H-series	200-325	Tke 2-2	40	25	8
7.5kw	Revive / H-series	250-370	Tke 2-2	40	31.3	8
9kw	Revive / H-series	325-450	Tke 2-2	50	37.5	8
10kw	Apex	400-625	Tke2-2	50	41.6	8
12kw	Apex	425-700	Tke 3	70	50	6
15kw	Apex	600-900	Tke 3	80	62.5	6

HEATER MODEL OR KW	208V HEATERS (3 PHASE)	RECOMMENDED ROOM SIZES CUBIC FEET	CONTROL (SPECIFY INDOOR OR OUTDOOR CONTACTOR)	CIRCUIT BREAKER	ACTUAL AMPS DRAWN	WIRE SIZE 90C COPPER WIRE
6kw	Revive	200-325	Tke 2-3	30	16.7	10
7.5kw	Revive	250-370	Tke 2-3	30	20.8	10
9kw	Revive / H-series	325-450	Tke 2-3	40	25	8
12kw	Apex	425-700	Tke 2-3 / Tke24D	50	33.4	8
15kw	Apex	600-900	Tke3 / Tke24D	50	41.7	8
18kw	Apex	690-1200	Tke 24D / Tke3	60	48	6

HEATER MODEL	DISTANCE TO COMBUSTIBLES
C-Series	4'' - front / 1'' corner
H-Series	4''
Revive Slim	3.5''
Revive	3.5''
F-Series	4''
Apex Mini	3.5''
Apex	5.5"